

Boom Lift

HB3500

Height: 0.26 ~ 3.5m Max Output: 6.3PS **Turning Ångle: L/R18°**

Equiped with choke in hand & Safety function

1Travel clutch lock

②Starting safe mechanics

3Control travel speed mechanics

Open cover WITHOUT tool





choke

cover

More Safety Style

Travel clutch lock, Starting safety mechanics, Control travel speed mechanics, and Safety gard give you safer work.

Simple operation System

- ▶It is easy to work turning and up-down of the boom by pedal side your foot.
- ◆It is smooth to restart the engine for equiping with choke lever in hand NEWLY.

Improvement in Mentenance

- ▶Rising cylinder lock mechanics gives you safer inspection & mentenance to fix the boom.
- It is easy to inspect and repaire the engine cover without tool.

More Comfortable operation

- To reduce swing & noise at time of work to adopt the rubber to keep from swing.
- ▶Variety of options to choose.

SPECIFICATIONS

of Edit Toxi Toxio				
MODEL		HB350M		
FULL LENGTH		3180mm	OPERATION	SIDE CLUTCH
FULL WIDTH		1280mm	CRAWLER SIZE	160 x 1324mm
FULL HEIGHT		1295mm	CRAWLER DIST.	1120mm
WEIGHT		403 k g	BRAKE	INTERNAL EXPATION
MAX LOAD CAPACITY		100 k g	ENGINE MODEL	MITSUBISHI GB180LE
GONDOLA SIZE		470 x 585	TYPE	AIR COLD OHV GASOLINE ENGINE
MINI HEIGHT		260mm	CRUISE OUTPUT	3.4 kw(4.7 ps) /1800rpm
MAX HEIGHT		3500mm	MAX OUTPUT	4.6 kw(6.3 ps
SYSTEM		BOOM (HYDRAULIC)	STARTER	CELL (RECOIL)
TURNING ANGLE		L/R18°	FUEL TANK	3.6L
NUMBER OF GEAR		F 1GEAR • R 1GEAR	BATTERY	30A19R
SPEED	F	TRAVELING 1.8km/h	OPTION	SHEET COVER CONTAINER WEIGHT
		BOOM IN OP 0.9km/h		CHAIR SHEET
	R	TRAVELING 1.8km/h		
		BOOM IN OP 0.9km/h		



- ●THESE SPECIFICATIONS, APPEARNAGE OF THE MACHINE IN THIS CATALOGUE MAY CHANCE WITHOUT ANY NOTICE.
- ●WORKING CAPACITY DEPENDS ON WORKING CONDITION AND OTHER CONDITIONS

CORPORATION

285 KOIKE, TSUBAME-CITY, NIIGATA-PREF 959-1276 JAPAN

URL: http://www-e-fujii.co.jp