

SNOWBLOWER



Happy removing with FULL outfit!

■Stepless with the HST lever

Operation speed can be controlled steplessly with the HST lever. Smooth switching between forward and backward movement.

■Electircal Power Chute

It is easy to control the throwing distance and direction with one electrical lever.

■Free Lock Lever

The auger part can be moved up and down effortlessly with a power-assist lever.

■ SPECIFICATIONS

MODEL	SG810M
SNOW REMOVING WIDTH	800 _{mm} /31.5inc
AUGER CASE HIGHT	510mm/20inc
MAXIMUM WORKING CAPACITY	60t/h
SNOW REMOVING DISTANCE	15m/13.7yard
LENGTH×WIDTH×HIGHT	1470x800x1160mm/58x31.5x45.7
WEIGHT	168ку/370 гь
MODEL OF ENGINE	MTSUBISHI GM301LE
TYPE OF ENGINE	AIR COOLED SINGLE CYLINDER
	OHV ENGINE (GASOLINE)
MAXIMUM OUTPUT	7.4kw/10.0ps/10.1hp
FUEL TANK CAPACITY	6.0L/1.6gal
STARTER	ELECTRIC
LIFT METHOD OF AUGER	LEVER(FREE LOCK)
SNOW REMOVING DIRECTION/DISTANCE	ELECTRIC
SPEEDS	HST(STEPLESS)
HEAD LIGHT	STANDARD EQUIPMENT
this satelesses been a seen	Ibilita ta abasas

*These specifications, appearances and all other contents of this catalogue have a possibility to change without notice for an improvement. **Working capacity depends on snow condition and other conditions. **The contents of this catalogue are as AUGUST 2004.



● DO RIGHT OPERATION FOR SAFETY WORK

●READ OPERATION MANUAL CAREFULLY AND UNDER STAND THE CONTENTS OF THE MANUAL WELL BEFORE USING MAVHINE FOR RIGHT AND SAFETY WORK.

FUJII CORPORATION

285 KOIKE TSUBAME-CITY NIIGATA-PREF, JAPAN
TEL +81-256-64-5512 FAX +81-256-64-5763
e-mail:eigyo@e-fujii.co.jp